



DOORBIRD
2-WIRE ETHERNET POE
CONVERTER A1071








The DoorBird 2-Wire Ethernet PoE Converter is probably the world's smallest and most powerful converter. It allows you to transfer network data (Ethernet) and power (PoE) with a simple two-wire cable over long distances. For example; existing buildings with a simple two-wire bell wire can be equipped with network technology without having to retrofit any network cables.

## THE FEATURES

- · Use of existing cabling
- Only a two-wire cable required for both data transmission and power supply (PoE)
- Compact design, robust metal housing
- Easy and fast installation



Operating conditions       -25 to 55°C / -13 to 131°F         Speed       Up to 60 mbit/s at maximum transmission range         Latency       - 0.01 ms         Connectors       1x RJ45, 2x screw terminals         PoE       PoE 802.3 af/at Mode-A and PoE +, up to 30 W         Data line pair       1/2 (+), 3/6 (-)         Range       80 meters / 262 feet with unshielded two-wire cable         Scope of delivery       1 x DoorBird 2-Wire Ethernet PoE Converter Sender 1 x DoorBird 2-Wire Ethernet PoE Converter Receiver 1 x DIN-Rail adapter         Required accessories       2 x Network cable, IEEE 802.3 af/at PoE Switch or PoE Injector, e.g. DoorBird Gigabit PoE Injector, D-Link DGS-1008P or TPLink TL-PoE150S         Compatible with all DoorBird IP Video Door Stations.       Compatible with all DoorBird IP Video Door Stations.         Approvals       CE, FCC, RoHS, IP50         Weather-proof       No         Weight       140 g         EAN       4260423860360	Power supply	(IEEE 802.3 af/at), not included
Latency - 0.01 ms  Connectors 1x RJ45, 2x screw terminals  PoE 802.3 af/at Mode-A and PoE +, up to 30 W  Data line pair 1/2 (+), 3/6 (-)  Range 80 meters / 262 feet with unshielded two-wire cable  1 x DoorBird 2-Wire Ethernet PoE Converter Sender 1 x DoorBird 2-Wire Ethernet PoE Converter Receiver 1 x DIN-Rail adapter  2 x Network cable, IEEE 802.3 af/at PoE Switch or PoE Injector, e.g. DoorBird Gigabit PoE Injector, D-Link DGS-1008P or TPLink TL-PoE150S  Compatible with all DoorBird IP Video Door Stations.  Approvals CE, FCC, RoHS, IP50  Weather-proof No  Weight 140 g	Operating conditions	-25 to 55°C / -13 to 131°F
Connectors  1x RJ45, 2x screw terminals  PoE 802.3 af/at Mode-A and PoE +, up to 30 W  Data line pair  1/2 (+), 3/6 (-)  Range  80 meters / 262 feet with unshielded two-wire cable  1 x DoorBird 2-Wire Ethernet PoE Converter Sender 1 x DoorBird 2-Wire Ethernet PoE Converter Receiver 1 x DIN-Rail adapter  2 x Network cable, IEEE 802.3 af/at PoE Switch or PoE Injector, e.g. DoorBird Cigabit PoE Injector, D-Link DGS-1008P or TPLink TL-PoE150S  Compatible with all DoorBird IP Video Door Stations.  Approvals  CE, FCC, RoHS, IP50  Weather-proof  No  Weight  140 g	Speed	•
PoE	Latency	~ 0.01 ms
Data line pair  1/2 (+), 3/6 (-)  Range  80 meters / 262 feet with unshielded two-wire cable  1 x DoorBird 2-Wire Ethernet PoE Converter Sender 1 x DoorBird 2-Wire Ethernet PoE Converter Receiver 1 x DIN-Rail adapter  2 x Network cable, IEEE 802.3 af/at PoE Switch or PoE Injector, e.g. DoorBird Gigabit PoE Injector, D-Link DGS-1008P or TPLink TL-PoE150S  Compatible with all DoorBird IP Video Door Stations.  Approvals  CE, FCC, RoHS, IP50  Weather-proof  No  Weight  140 g	Connectors	1x RJ45, 2x screw terminals
Range  80 meters / 262 feet with unshielded two-wire cable  1 x DoorBird 2-Wire Ethernet PoE Converter Sender 1 x DoorBird 2-Wire Ethernet PoE Converter Receiver 1 x DIN-Rail adapter  2 x Network cable, IEEE 802.3 af/at PoE Switch or PoE Injector, e.g. DoorBird Gigabit PoE Injector, D-Link DGS-1008P or TPLink TL-PoE150S  Compatible with all DoorBird IP Video Door Stations.  Approvals  CE, FCC, RoHS, IP50  Weather-proof No  Weight  140 g	PoE	
Range    1 x DoorBird 2-Wire Ethernet PoE	Data line pair	1/2 (+), 3/6 (-)
Converter Sender  1 x DoorBird 2-Wire Ethernet PoE Converter Receiver 1 x DIN-Rail adapter  2 x Network cable, IEEE 802.3 af/at PoE Switch or PoE Injector, e.g. DoorBird Gigabit PoE Injector, D-Link DGS-1008P or TPLink TL-PoE150S  Compatible with all DoorBird IP Video Door Stations.  Approvals  CE, FCC, RoHS, IP50  Weather-proof No  Weight  140 g	Range	·
Switch or PoE Injector, e.g. DoorBird Gigabit PoE Injector, D-Link DGS-1008P or TPLink TL-PoE150S  Compatible with all DoorBird IP Video Door Stations.  Approvals  CE, FCC, RoHS, IP50  Weather-proof No  Weight  140 g	Scope of delivery	Converter Sender 1 x DoorBird 2-Wire Ethernet PoE Converter Receiver
Approvals CE, FCC, RoHS, IP50  Weather-proof No  Weight 140 g	Required accessories	Switch or PoE Injector, e.g. DoorBird Gigabit PoE Injector, D-Link DGS-1008P or TPLink TL-PoE150S  Compatible with all DoorBird IP Video
Weather-proof No Weight 140 g	Approvala	
Weight 140 g	Approvais	CE, FCC, ROHS, IP50
-	Weather-proof	No
EAN 4260423860360	Weight	140 g
	EAN	4260423860360