SLIDING GATES 230V AC


230V AC



Code	Description	Pcs/pallet
R30/804	Electromechanical motor 230V AC irreversible ideal for sliding gates up to 800 kg with built-in control unit H70, optical encoder and magnetic limit switch.	44

Product technical specifications	R30/804
Max gate weight	**800 kg**
Power line supply	**230V AC - 50Hz**
Motor power supply	**230V AC**
Power rating	**350W**
Frequency of use	**50%**
Thrust	**500N**
Operating temperature	**-20+55°C**
Protection level	**IP43**
Reductor Type	**Irreversible**
Manoeuvre speed	**9.5 m/min (0.16 m/s)**
Motor thermal protection	**150°C**
Incorporated condenser	**15 µF**
Limit switch	**Magnetic**
Onboard control unit	**H70/104AC**
Encoder	**Optical**
Type exit gear	**Z17/mod 4**
Maximum dimension product in mm (L x W x H)	**325 x 162 x 295**
Product weight packed (Kg)	**15,3**
Number items per pallet	**44**

TECHNICAL IMAGE




PACKAGING INFORMATION




Size in cm: Lenght: 35.5 - Widht. 21 - Heigth. 31.5

ROGER TECHNOLOGY
AUTOMAZIONI EVOLUTE

PRODUCT DIMENSIONS AND PREPARING FOR INSTALLATION




DIMENSIONS




PREDISPOSITION FOR STANDARD INSTALLATION


PRODUCT ACCESSORIES



KT210
Fixing plate with stay bolts and screws for R30 series.




KT212
Raised fixing plate for R30 series (+3,5 cm).




KT213
Fixing plate and angles bars kit for R30 series.



GA550
Galvanised steel rack 22x22x1000 module 4.




GA551
Galvanised steel rack 30x12x1000 module 4 with spacers and screws.




GA553
Nylon rack module 4 with 6 connectors L.1000.



GA554
Pocket of 6 spacers (2,5 Cm) and screws.



LT328
Z17 mod. 4 Pinion with increased thickness H.38 for series R30 - G30 - E30



MC775
Kit magnetic limit switch for control unit H70/103AC, H70/104AC, B70/1DC, B70/1DCHP.



R99/C/001
Signboard Automatic Opening".

ROGER TECHNOLOGY
Via S. Botticelli, 8 - 31021, Bonisiolo di Mogliano Veneto (TV) - ITALIA P.IVA 01612340263 Tel. +39 041 5937023 Fax +39 041 5973023
info@rogertechnology.it - www.rogertechnology.it

ROGER TECHNOLOGY
AUTOMAZIONI EVOLUTE