PRODUCT TECHNICAL DATASHEET: R21/351


230V AC




Code	Description	Pcs/pallet
R21/351	Electromechanical underground motor 230V AC irreversible ideal for swing gates with leaf up to 3,5 mt. Standard version with 2 mt cable.	50

Product technical specifications	R21/351
Power line supply	**230V AC - 50Hz**
Motor power supply	**230V AC**
Power rating	**200W**
Frequency of use	**30%**
Torque	**300 N m**
Operating temperature	**-20+55°C**
Protection level	**IP67**
Reductor Type	**Irreversible**
Manoeuvre speed	**1,2 Rpm**
Opening time at 90°	**19 s**
Motor thermal protection	**150°C**
Limit switch	**Mechanical stoppers**
Encoder	**-**
Maximun opening	**105° (optional 125° - 360°)**
Power supply cable length	**2m**
Bearing on main shaft	**Standard**
Maximum dimension product in mm (L x W x H)	**345 x 224 x 144**
Product weight packed (Kg)	**14,1**
Number items per pallet	**50**

PRODUCT DIMENSIONS



DIMENSIONS



DIMENSIONS

PRODUCT ACCESSORIES



FU100
Cold galvanised foudation box and lid.




FU101
Hot galvanised foundation box and lid.




FU102
Hot galvanised foundation box and inox lid.




FU103
Inox AISI 304 foundation box and lid.



LT300
Levers for opening up to 125°.



LT301
Levers for opening up to 360°.




LT301/R
Levers for opening up to 360° , with reinforced chain.




LT300/90SX
Levers for opening up to 125° - 90° turned - left




LT300/90DX
Levers for opening up to 125° - 90° turned - right




LT327/SC
Pinion gear ¾ Z13 of adaptation in pinion ombining ¾ Z16



RL650
Release system with standard lever.



RL650/R
Release system with standard lever,reinforced steel version.



RL651
Release system with european cylinder key.



RL663
Long release lever for underground.



R99/C/001
Signboard Automatic Opening".

ROGER TECHNOLOGY
Via S. Botticelli, 8 - 31021, Bonisiolo di Mogliano Veneto (TV) - ITALIA P.IVA 01612340263 Tel. +39 041 5937023 Fax +39 041 5973023
info@rogertechnology.it - www.rogertechnology.it